2.1.4 Acids

An acid releases H+ ions in aqueous solution

The most common strong acids are : Hydrochloric (HCl), sulphuric (H_2SO_4) and nitric (HNO $_3$) acid; Ethanoic acid CH $_3$ COOH is a weak acid

There are several definitions of acids we use in chemistry. One we use later in the course is the Bronsted-Lowry acid which is a defined as a proton (H⁺) donor

Bases and Alkalis

Bases neutralise acids. Common bases are metal oxides, metal hydroxides and ammonia.

An Alkali is a soluble base that releases OH- ions in aqueous solution;

The most common alkalis are sodium hydroxide (NaOH), potassium hydroxide (KOH) and aqueous ammonia (NH₃)

The Bronsted- Lowry base is defined as a proton (H⁺) acceptor

A base readily accepts H⁺ ions from an acid: eg OH⁻ ions accepts an H⁺ ion forming H₂O NH₃ accepts an H⁺ ion forming NH₄⁺ ion

Strong and weak acids

Strong acids completely dissociate when dissolved in water

Weak acids only slightly dissociate when dissolved in water, giving an equilibrium mixture

Neutralisation Reactions

Neutralisation reaction form salts

A **Salt** is formed when the H⁺ ion of an acid is replaced by a metal ion or an ammonium ion

Common Neutralisation Reaction Equations

HCl + NaOH → NaCl +H₂O

 $2HNO_3 + Mg(OH)_2 \rightarrow Mg(NO_3)_2 + 2H_2O$

 $H_2SO_4 + 2NaOH \rightarrow Na_2SO_4 + 2H_2O$

2HCl + CaO → CaCl₂ +H₂O

HCl + NH₃ → NH₄Cl

Acid + Carbonate → Salt + Water + Carbon Dioxide

 $H_2SO_4 + K_2CO_3 \rightarrow K_2SO_4 + CO_2 + H_2O$

 $2HCI + Na₂CO₃ \rightarrow 2NaCI + CO₂ + H₂O$

 $2HCl + CaCO_3 \rightarrow CaCl_2 + CO_2 + H_2O$

Observations: In carbonate reactions there will be Effervescence due to the CO₂ gas evolved and the solid carbonate will dissolve

Titrations

The method for carrying out the titration

- •rinse equipment (burette with acid, pipette with alkali, conical flask with distilled water)
- •pipette 25 cm³ of alkali into conical flask
- •touch surface of alkali with pipette (to ensure correct amount is added)
- •adds acid solution from burette
- •make sure the jet space in the burette is filled with acid
- •add a few drops of indicator and refer to colour change at end point
- •phenolphthalein [pink (alkali) to colourless (acid): end point pink colour just disappears] [use if NaOH is used]
- •methyl orange [yellow (alkali) to red (acid): end point orange] [use if HCl is used]
- •use a white tile underneath the flask to help observe the colour change
- •add acid to alkali whilst swirling the mixture and add acid dropwise at end point
- •note burette reading before and after addition of acid
- •repeats titration until at least 2 concordant results are obtained- two readings within 0.1 of each other

Working out average titre results

Only make an average of the concordant titre results

If 2 or 3 values are within 0.10cm³ and therefore concordant or close then we can say results are accurate and reproducible and the titration technique is good/ consistent

Recording results

- •Results should be clearly recorded in a table
- •Result should be recorded in full (i.e. both initial and final readings)
- •Record titre volumes to 2dp (0.05 cm³)

Safety precautions

Acids and alkalis are corrosive (at low concentrations acids are irritants)

Wear eye protection and gloves If spilled immediately wash affected parts after spillage

If substance is unknown treat it as potentially toxic and wear gloves.

If the jet space is not filled properly prior to commencing the titration it will lead to errors if it then fills during the titration, leading to a larger than expected titre reading.

A conical flask is used in preference to a beaker because it is easier to swirl the mixture in a conical flask without spilling the contents.

Indicators are generally weak acids so we only add a few drops of them. If too much is added it will affect the titration result

Distilled water can be added to the conical flask during a titration to wash the sides of the flask so that all the acid on the side is washed into the reaction mixture to react with the alkali. It does not affect the titration reading as water does not react with the reagents or change the number of moles of acid added.

Common Titration Equations

 $CH_{3}CO_{2}H + NaOH \rightarrow CH_{3}CO_{2}^{-1}Na^{+} + H_{2}O$ $H_{2}SO_{4} + 2NaOH \rightarrow Na_{2}SO_{4} + 2H_{2}O$ $HCI + NaOH \rightarrow NaCI + H_{2}O$ $NaHCO_{3} + HCI \rightarrow NaCI + CO_{2} + H_{2}O$ $Na_{2}CO_{3} + 2HCI \rightarrow 2NaCI + CO_{2} + H_{2}O$

Titrating mixtures

If titrating a mixture to work out the concentration of an active ingredient it is necessary to consider if the mixture contains other substances that have acid base properties.

If they don't have acid base properties we can titrate with confidence.

Testing batches

In quality control it will be necessary to do titrations/testing on several samples as the amount/concentration of the chemical being tested may vary between samples.

Safely dealing with excess acid

Sodium hydrogen carbonate (NaHCO₃) and calcium carbonate (CaCO₃) are good for neutralising excess acid in the stomach or acid spills because they are not corrosive and will not cause a hazard if used in excess. They also have no toxicity if used for indigestion remedies but the CO₂ produced can cause wind. Magnesium hydroxide is also suitable for dealing with excess stomach acid as it has low solubility in water and is only weakly alkaline so not corrosive or dangerous to drink (unlike the strong alkali sodium hydroxide). It will also not produce any carbon dioxide gas.

Example 1: A 25.0cm³ sample of vinegar was diluted in a 250cm^3 volumetric flask. This was then put in a burette and 23.10cm^3 of the diluted vinegar neutralised 25.0 cm³ of 0.100 M NaOH. What is the concentration of the vinegar in gdm^{-3} ?

CH₃CO₂H + NaOH → CH₃CO₂-Na+ + H₂O

Step 1: work out amount, in mol, of sodium hydroxide amount = conc x vol

 $= 0.10 \times 0.025$

= 0. 00250 mol

Step 2: use balanced equation to give moles of $\mathrm{CH_{3}CO_{2}H}$

1 moles NaOH : 1 moles CH_3CO_2H So 0.00250 NaOH : 0.00250 moles CH_3CO_2H

Step 3 work out concentration of diluted ${\rm CH_3CO_2H}$ in 23.1 (and 250 ${\rm cm^3}$)in moldm $^{\text{-}3}$

conc= amount/Volume

= 0.00250 / 0.0231

 $= 0.108 \text{ mol dm}^{-3}$

Step 4 work out concentration of original concentrated $\rm CH_3CO_2H$ in $25\rm cm^3$ in $\rm moldm^{-3}$

conc = $0.108 \times 10 = 1.08 \text{ mol dm}^{-3}$

Step 5 work out concentration of CH₃CO₂H in original concentrated 25 cm³ in gdm⁻³

conc in $gdm^{-3} = conc in mol dm^{-3} x Mr$

 $= 1.08 \times 60 = 64.8 \text{ g dm}^{-3}$

Example 2. An unknown metal carbonate reacts with hydrochloric acid according to the following equation. $M_2CO_3(aq) + 2HCl(aq) \rightarrow 2MCl(aq) + CO_2(g) + H_2O(l)$ A 3.96 g sample of M_2CO_3 was dissolved in distilled water to make 250 cm³ of solution. A 25.0 cm³ portion of this solution required 32.8 cm³ of 0.175 mol dm⁻³ hydrochloric acid for complete reaction. Calculate the Mr of M_2CO_3 and identify the metal M

1. Calculate the number of moles of HCl used

amount = conc x vol

= 0.175 x 0.0328

= 0. 00574 mol

2. Work out number of moles of $\rm M_2CO_3^{}\,$ in 25.0 cm 3 put in conical flask

use balanced equation to give moles of M₂CO₃

2 mol HCl : 1 mol M_2CO_3

So 0. 00574 NaOH : 0.00287 moles $\mathrm{M_2CO_3}$

3. Calculate the number of moles $\rm M_2CO_3\,acid$ in original $\rm~250\,cm^3$ of solution

Moles in $250 \text{cm}^3 = 0.00287 \times 10$ =0.0287

4. work out the Mr of M₂CO₃

Mr= mass / amount

= 3.96/ 0.0287= 138.0

5. Work out Ar of M = (138-12-16x3)

2

Ar of M = 39 M= potassium

Common Titration Equations

 $CH_3CO_2H + NaOH \rightarrow CH_3CO_2^-Na^+ + H_2O$

 $H_2SO_4 + 2NaOH \rightarrow Na_2SO_4 + 2H_2O$

HCl + NaOH → NaCl +H₂O

NaHCO₃ + HCl → NaCl + CO₂ + H₂O

 $Na_2CO_3 + 2HCI \rightarrow 2NaCI + CO_2 + H_2O$

Example 3

950 mg of impure calcium carbonate tablet was crushed. 50.0 cm 3 of 1.00 mol dm $^{-3}$ hydrochloric acid, an excess, was then added. After the tablet had reacted, the mixture was transferred to a volumetric flask. The volume was made up to exactly 100 cm 3 with distilled water. 10.0 cm 3 of this solution was titrated with 11.1cm 3 of 0.300 mol dm $^{-3}$ sodium hydroxide solution.

What is the percentage of CaCO₃ by mass in the tablet?

1. Calculate the number of moles of sodium hydroxide used

amount = conc x vol

 $= 0.30 \times 0.0111$

= 0.00333 mol

2. Work out number of moles of hydrochloric acid left in 10.0 cm³

use balanced equation to give moles of HCl

1 mol NaOH : 1 mol HCl

So 0.00333 NaOH: 0.00333 moles HCl

3. Calculate the number of moles of hydrochloric acid left in 100 cm³ of solution

Moles in $100 \text{cm}^3 = 0.00333 \text{ x}10$ = 0.0333

4. Calculate the number of moles of HCl that reacted with the indigestion tablet.

In original HCl 50.0 cm³ of 1.00 mol dm⁻³ there is 0.05moles

moles of HCl that =0.05 -0.0333 reacted with the =0.0167

indigestion tablet.

5 Use balanced equation to give moles of CaCO₃

 $CaCO_3(s) + 2HCI(aq) \rightarrow CaCI_2(aq) + CO_2(g) + H_2O(l)$

2 mol HCl : 1 mol CaCO₃

So 0.0167 HCl: 0.00835 moles CaCO₃

6. work out the mass of CaCO₃ in original tablet

mass= amount x Mr

 $= 0.00835 \times 100 = 0.835 g$

percentage of

 $CaCO_3$ by mass in = 0.835/0.950 x100

the tablet

= 87.9 %

Uncertainty

Readings and Measurements

Readings

the values found from a single judgement when using a piece of equipment

Measurements

the values taken as the difference between the judgements of two values (e.g. using a burette in a titration) The uncertainty of a reading (one judgement) is at least ± 0.5 of the smallest scale reading. The uncertainty of a measurement (two judgements) is at least ± 1 of the smallest scale reading.

Calculating Apparatus Uncertainties

Each type of apparatus has a sensitivity uncertainty

•balance \pm 0.001 g •volumetric flask \pm 0.1 cm³ •25 cm³ pipette \pm 0.1 cm³

•burette (start & end readings and end point) \pm 0.15 cm³

Calculate the percentage error for each piece of equipment used by

% uncertainty = \pm uncertainty x 100 Measurement made on apparatus

e.g. for burette

% uncertainty = 0.15/average titre result x100

To calculate the maximum percentage apparatus uncertainty in the final result add all the individual equipment uncertainties together.

To decrease the apparatus uncertainties you can either decrease the sensitivity uncertainty by using apparatus with a greater resolution (finer scale divisions) or you can increase the size of the measurement made.

Uncertainty of a measurement using a burette. If the burette used in the titration had an uncertainty for each reading of +/- 0.05 cm³ then during a titration two readings would be taken so the uncertainty on the titre volume would be +/- 0.10 cm³. Then often another 0.05 is added on because of uncertainty identifying the end point colour change

Reducing uncertainties in a titration

Replacing measuring cylinders with pipettes or burettes which have lower apparatus uncertainty will lower the error

To reduce the uncertainty in a burette reading it is necessary to make the titre a larger volume. This could be done by: increasing the volume and concentration of the substance in the conical flask or by decreasing the concentration of the substance in the burette.

If looking at a series of measurements in an investigation the experiments with the smallest readings will have the highest experimental uncertainties.

Reducing uncertainties in measuring mass

Using a more accurate balance or a larger mass will reduce the uncertainty in weighing a solid Weighing sample before and after addition and then calculating difference will ensure a more accurate measurement of the mass added.

Calculating the percentage difference between the actual value and the calculated value

If we calculated an Mr of 203 and the real value is 214, then the calculation is as follows: Calculate difference 214-203 = 11% = $11/214 \times 100$

=5.41%

If the %uncertainty due to the apparatus < percentage difference between the actual value and the calculated value then there is a discrepancy in the result due to other errors.

If the %uncertainty due to the apparatus > percentage difference between the actual value and the calculated value then there is no discrepancy and all errors in the results can be explained by the sensitivity of the equipment.